

Laundry-Scull

Basic Features

- There is a "cool down" cooling system which prevents wrinkling, hardening and heat shock.Thanks to the double direction rotation feature of the drum, it is ensured that the laundry dry in a shorter time.
- By the body insulation, the prevention of heat losses is ensured.
- There is an air leak prevention, custom-made gasket in the glazed inspection cover which is made by a pressing machine.



Ürün Kodu Product code	PMK-ÇK20	PMK-ÇK30	PMK-ÇK40	PMK-ÇK50	PMK-ÇK60
Kapasite Capacity	20 kg	30 kg	40 kg	50 kg	60 kg
Tambur Çapı Drum Diameter	1145 mm	1145 mm	1145 mm	1145 mm	1145 mm
Tambur Derinliği Drum Depth	450 mm	670 mm	780 mm	980 mm	910 mm
Tambur Hacmi Drum Volume	463 lt	689 lt	802 lt	1008 lt	1207 lt
Tambur Motor Gücü Drum Motor Power	0,75 kw 1500 dv/dk	0,75 kw 1500 dv/dk	0,75 kw 1500 dv/dk	0,75 kw 1500 dv/dk	0,75 kw 1500 dv/dk
Fan Motor Gücü Fan Motor Power	0,75 kw 3000 dv/dk	0,75 kw 3000 dv/dk	0,75 kw 3000 dv/dk	0,75 kw 3000 dv/dk	0,75 kw 3000 dv/dk
Isıtma Gücü Heating Power	18 kw	18 kw	22,5 kw	27 kw	27 kw
Isitma Tipi Heating Type	Elektrik	Elektrik	Elektrik	Elektrik	Elektrik
Kablo Kesiti* Cable cross section*	4x6 mm²	4x6 mm²	4x10 mm ²	4x10 mm ²	4x10 mm ²
Ebat Dimensions	1400x800x800 mm	1400x1050x800 mm	1400x1160x800 mm	1400x1350x800 mm	1400x1300x800 mm
Ağırlık Weight	341 kg	390 kg	440 kg	510 kg	550 kg
Fiyat Price	4750 €	5250 €	5950 €	7850 €	10.850 €



Laundry Washing & Spinning Machine

Basic Features

- The inner and outer drum, glazed inspection cover and outer cover panels, are made of AISI 304 Quality 18/8 CR-NI stainless steel.
- There is a leak prevention, custom-made gasket in the machine door. Further, it's ensured that the machine doesn't work when its door is open, and the door of a working machine won't open due to the door locking system.

• The machine is controlled by an electronic digital display mounted on the front control panel. Although there are 25 fixed programs on the machine, it provides unlimited optional programs and electricity, water

and time saving.

- There is a safety system which makes the machine stop automatically, for the purpose of preventing damage because of a vibration that could occur, arising from an unforeseen cause during operation.
- It provides minimum vibration and balance, thanks to the improved spring, damper and pulley system.



Ürün Kodu Product code	PMK-ÇYS20	PMK-ÇYS30	PMK-ÇYS40	PMK-ÇYS50	PMK-ÇYS60
Kapasite Capacity	20 kg	30 kg	40 kg	50 kg	60 kg
Tambur Çapı Drum Diameter	700 mm	800 mm	900 mm	995 mm	995 mm
Tambur Derinliği Drum Depth	550 mm	610 mm	635 mm	650 mm	780 mm
Tambur Hacmi Drum Volume	211 Lt	306 Lt	403Lt	505 Lt	606 Lt
Motor Gücü Motor Power	3 kw	4 kw	5,5 kw	7,5 kw	7,5 kw
Isıtma Gücü Heating Power	13,5 kw	18 kw	22,5 kw	27 kw	36 kw
Isitma Tipi Heating Type	Elektrik	Elektrik	Elektrik	Elektrik	Elektrik
Kablo Kesiti* Cable cross section*	4x6 mm²	4x6 mm ²	4x10 mm ²	4x10 mm ²	4x10 mm ²
Su Girişi Water Input	3/4 "	3/4 "	3/4 "	3/4 "	3/4 "
Ebat Dimensions	1100x1335x1350 mm	1200x1350x1480 mm	1310x1400x1710 mm	1390x1430x1800 mm	1390x1530x1800 mm
Ağırlık Weight	613 kg	757 kg	938 kg	1120 kg	1210 kg
Fiyat Price	7800 €	8850 €	10.850 €	14.850 €	18.100 €

^{*}Cable cross section is specified in minimum ratio. Cross sections should be increased according to the cable length.

Basic Features

- Outer coverings are made of electrostatic powder coated DKP sheet material.
- Speed adjustment is available.
- There is a manual operating lever to remove the laundry from the machine in case of power cuts.
- Thanks to the lock system, the machine is ensured not to operate while the covers are open.
- There is a working system that emphasizes silent and easy use.
- Cable cross section is specified in minimum ratio. The cross section should be increased according to the cable length.



Ürün Kodu Product code	PMK-BSÜ.18	PMK-BSÜ.20
Silindir Boyu (mm) Cylinder Length (mm)	1800	2000
Silindir Çapı (mm) Cylinder Diameter (mm)	600	600
Motor Gücü (kw) Motor power (kw)	0,75	0,75
Isitma Gücü (kw) Heating Power (kw)	22,5	22,5
Isitma Tipi Heating Type	Elektrik / Electric	Elektrik
Kablo Kesiti (mm2) Cable cross section (mm2)	4x10	4x10
Genişlik (mm2) Width (mm2)	22410	22610
Derinlik (mm) Depth (mm2)	1160	1160
Yükseklik (mm) Height (mm2)	1150	1150
Ağırlık (kg) Weight (kg)	825	841 kg
Fiyat €	6800 €	7550 €



Press Ironing Machine & Narrow Ironing Table Within Boiler



Press Iron Basic Features

- The top ironing jaw is made of cast aluminum and steam is distributed evenly.
- Thanks to specially manufactured steam valves, it provides the opportunity to iron in desired form by using high-temperature, dry steam.
- Print is set.
- There are foot control pedals for locking and unlocking the lower cushion of the upper jaw and giving steam.

Press Iron Basic Features

- Ergonomic design and wheeled legs provide convenience in the transportation and placement of the machine.
- Steam is ready in a short time (8 minutes) and
- The table temperature is adjusted with a thermostat and offers the possibility of ironing without interruption for a long time.
- It automatically transfers water from the water tank it contains.
- Thanks to its combined system, it does not require an additional steam generator.



Kendinden Kazanlı Paskala Ütü Boiler



Ürün Kodu Product Code	PMK-PÜ21
Pompa Gücü (kw) Pump Power (kw)	0,75
Isıtma Gücü (kw) Heating Power (kw)	20
Buhar Basıncı (Bar) Steam Pressure (Bar)	4
Buhar Kapasitesi (kg/h) Steam Capacity (kg/h)	24
Genişlik (mm) Width (mm)	1450
Derinlik (mm) Depth (mm)	1350
Yükseklik (mm) Height (mm)	1450
Ağırlık (kg) Weight (kg)	380
Fiyat € Price €	4750 €

illinoar i cataroc	
Ürün Kodu Product Code	PMK-PÜ22
Pompa Gücü (kw) Pump Power (kw)	0,37
Vakum Motoru (kw) Vacuum Motor (kw)	0.37
Isıtma Gücü (kw) Heating Power (kw)	5
Çalışma Basıncı (Bar) Working Pressure (Bar)	3.5
Buhar Kapasitesi (kg/h) Steam Capacity (kg / h)	24
Su Deposu Hacmi (Lt) Water Tank Volume (Lt)	30
Genişlik (mm) Width (mm)	1400
Derinlik (mm) Depth (mm)	500
Yükseklik (mm) Height (mm)	900
Ağırlık (kg) Weight (kg)	85
Fiyat € Price €	2000 €

Glass Washer & Cunter-bottom Type Dishwashers

URCO DAZAAR D)

Glass Washer Basic Features

- Water inlet 3/4"
- Power supply is electricity
- Control type is analog
- The volume of wash tank 17 Lt
- The volume of boiler tank 3.6 Lt
- Wash temperature at 50-55 $^{\circ}$ C
- Rinse temperature at 70-75 ° C
- Consumes 0.6 liters of water each rinse
- Internal cabinet height 185 mm
- Wash motor power 0.26 kW
- Tank resistance power is 1 kW
- Boiler resistance power is 2 kW
- Net weight 37 Kg

Cunter-bottom Type Basic Features

- Water inlet 3/4"
- Power supply is electricity
- Control type is analog
- The volume of wash tank 27 Lt
- The volume of boiler tank 6.5 Lt
- Wash temperature at 50-55 ° C
- Rinse temperature at 80-85 ° C
- Consumes 0.8 liters of water each rinse
- Internal cabinet height 340 mm
- Wash motor power 0.6 kW
- Tank resistance power is 2 kW
- Boiler resistance power is 2 kW
- Net weight 60 Kg



amaşırhane-Bulaşık Laundry-Scullery

Ürün Kodu Product Code	Enerji Tipi Energy Type	Kapasite (Ürün/Saat) Capacity (Item/Hour)	Ebat (cm) Dimensions (cm)	Ağırlık (Kg.) Weight (Kg.)	Fiyat Price
M038-1	4	800	45x50x65		1300 €
M036-B	4//	500	60x60x82	60	1390 €
M036-DS		() =	-	-	230 €



Giotin Type Dishwashers



Basic Features

- Water inlet 3/4"
- Power supply is electricity
- Control type is analog The volume of wash tank 17 Lt
- The volume of boiler tank 3.6 Lt
- Wash temperature at 50-55 $^{\circ}$ C
- Rinse temperature at 70-75 ° C
 Consumes 0.6 liters of water each rinse
 Internal cebine! height 185 mm
- Wash motor power 0.26 kW
- Tank resistance power is 1 kW
 Boiler resistance power is 2 kW
- Net weight 95 Kg





Teknik Özellikler | Technical Features

Ürün Kodu Product Code	Enerji Tipi Energy Type	Güç (kW/) Power (kW/)	Kapasite (Tabak/Saat) Capacity (Plate/Hour)	Ebat (cm) Dimensions (cm)	Ağırlık (Kg.) Weight (Kg.)	Fiyat Price
M036-1	4	1,5	1000	65x82x140	95	1900 €
PMK.TB.01 ◎	-	-	-		_	
PMK.TB.02 11	-	-	-			////
PMK.TB.03	_	_	_	_		

For Basket Prices, please submit your price request.

Glass Washer Basic Features

- Water inlet 3/4"
- Power supply is electricity
- Control type is analog The volume of wash tank 50+55 Lt
- The volume of boiler tank 18 Lt
- \bullet Wash temperature at 50-55 $^{\circ}$ C
- Rinse temperature at 50-55 ° C
 Consumes 0.6 liters of water each rinse
 Internal cabinet height 480 mm
- Wash motor power 1, 1 x2 kW
- Tank resistance power is 6 kWBoiler resistance power is 18 kW
- Net weight 255 Kg



್ಲ್	\geq
<u>=</u>	<u>e</u>
卒	듔
은	Š
=	\leq
≅ ∘	p
22	m

Teknik Özellikler Technical Features						
Ürün Kodu Product Code	Enerji Tipi Energy Type	Güç (kW/) Power (kW/)	Kapasite (Tabak/Saat) Capacity (Plate/Hour)	Ebat (cm) Dimensions (cm)	Ağırlık (Kg.) Weight (Kg.)	Fiyat Price
M036-T1	4	1,5	1500-2000	77x177,5x254	255	8900 €